Windows Server
How do I reach a Linux guest system under Hyper-V?

Problem:

You want to mount a Linux guest system under Hyper-V, but it is not reachable under the configured IP address.

Possible reasons:

- The IP address of the virtual machine is not in the same subnet of the host system.
- The MAC address of the guest system is defined as "static" in Hyper-V.

Solution:

Setup a host route on your guest system to the gateway.

Example CentOS/RedHat:

route add <IP-Adresse des Gateways>/32 dev eth0
route add default gw <IP-Adresse des Gateways>

Snares:

Please notice: You must set the routing motification again by booting of the Linux guest system e.g. with INIT script.

Further links (no guarantee of functionality):

- http://www.adminsehow.com/2011/09/gateway-on-a-different-subnet-on-linux/
- http://xmodulo.com/how-to-run-startup-script-automatically-after-network-interface-is-up-on-centos.html

---

We would like to say thank you to customer Sven S. for provisioning of this FAQ.

(c) 2026 EUserv Internet <support@euserv.de> | 2026-11-09 18:04
URL: https://faq.euserv.de/content/56/391/en/how-do-i-reach-a-linux-guest-system-under-hyper_v.html

(c) 2026 EUserv Internet <support@euserv.de> | 2026-11-09 18:04

URL: https://faq.euserv.de/content/56/391/en/how-do-i-reach-a-linux-guest-system-under-hyper_v.html

Windows Server

Unique solution ID: #1710
Author: EUserv Support
Last update: 2016-03-23 15:08

(c) 2026 EUserv Internet <support@euserv.de> | 2026-11-09 18:04

URL: https://faq.euserv.de/content/56/391/en/how-do-i-reach-a-linux-guest-system-under-hyper_v.html